



The PST-100 Spark Tester provides a quick and cost effective method of inspection on thick coatings and linings. Coating thicknesses of 3mm to 30mm can be tested.

It is widely used for testing butt-welded and overlap joints in the plastics & rubber, petro-chemical and pipeline construction industries.

The PST Accessory Kit has been specially created to offer a complete testing solution for most applications.

Other sizes and types of electrodes can be supplied, if required, for specific requirements. However, to ensure the stability of the output voltage, large electrodes should not be used.

**ACCESSORY KIT (ref: T51)** comprises:  
PST-100 unit 220/240V, in executive style case c/w spare HF Coil, spark gap setter, flexible probe, pointed probe, drum brush, 2 x 220mm insulated extension rods, gauze mesh electrode with adaptor, 150mm phosphor bronze brush electrode with adaptor and operating instructions.

## FEATURES

- Lightweight
- Mains Powered
- Adjustable output voltage
- Power limited output for operator safety
- Coating thicknesses of between 3mm - 30mm can be tested

## TECHNICAL SPECIFICATION

- Output voltage range: 10 - 55kV
- Output: Pulsed ring
- CE Compliant
- Mains voltage: 220/240V AC 50/60 Hz
- Weight (Unit only): 1.05Kg
- Dimensions (Unit only): 6cm wide x 20cm high x 27cm long
- Packed Weight (Accessory kit): 4.2Kg
- Dimensions (packed): 50cm x 14cm x 37cm

Note: Due to ongoing technical developments, all stated information is typical and is subject to change without notice or obligation

## AFTER SALES SERVICE / TECHNICAL SUPPORT

All Buckleys products are manufactured under the controls established by a quality management system that meets the requirements of BS EN ISO 9001:2008 and are supplied with a one year "back-to-base" warranty. The equipment is proven to be robust and reliable and will give years of service if maintained in accordance with our instructions.

Buckleys provide full repair facilities offering a fast turn-around service for customers equipment.

Advice on specific applications for all Buckleys products is available from our technical department. Contact us by telephoning, sending a fax or by e-mail using the contact details below.

**Buckleys (UVRAL) Ltd., Buckleys House, Unit G, Concept Court, Shearway Business Park, Shearway Road, Folkestone, Kent. CT19 4RG. UK**

**Tel: +44 (0)1303 278888 Fax: +44 (0)1303 274331  
e-mail: sales@buckleys.co.uk web site: www.buckleys.co.uk**